


- NOTE:
- ALL STRUCTURE IS FULLY WELDED WITH A NOMINAL FILLET OF 5mm
 - ALL EXTRUSIONS ARE OF GRADE 6063-T5 OR EQUIVALENT.
 - FILLER ALLOY IS GRADE 5356
 - ALL TIMBER IS TO BE TREATED WITH A SUITABLE PRESERVATIVE. (DECKING OIL ETC)
 - ALL FASTENERS ARE CORROSION RESISTANT STAINLESS STEEL.
 - ALL EXPOSED BOLTS ARE TO BE RECESSED INTO THE TIMBER BY COUNTER BORING.
 - ALL BOLT THREADS ARE TO BE TREATED WITH ANTI-SIEZE OR EQUIVALENT LUBRICATING COMPOUND, PRIOR TO FASTENING.
 - THIS DRAWING IS FOR A PONTOON OF TYPICAL DESIGN. ENGINEERING EVALUATION SHOULD BE PERFORMED FOR THE PONTOONS SUITABILITY FOR EACH PARTICULAR INSTALLATION.



**MARINE DOCK SYSTEMS
PTY LTD**

3.6m x 2.5m PONTOON
4x650L FLOATS

PONTOON-2600



| | | | | |
|-------|--------|-----|----------------|--------|
| SCALE | N.T.S. | DWG | A4-2600 | |
| DRAWN | JPM | REV | A | 7,7,99 |
| DATE | 7,7,99 | CHK | APP'D | |