



APPROX. WEIGHT-850kg

MARINE DOCK SYSTEMS
PTY LTD

4.1m x3.0m PONTON
4x 1200L FLOATS

PONTON-2493



NOTE:
 -PONTON IS DESIGNED IN ACCORDANCE WITH AS 3962-1991 GUIDELINES FOR DESIGN OF MARINAS. RESTRICTED ACCESS.
 -ALL WELDING IN ACCORDANCE WITH AS 1665-1992. WELDING OF ALUMINIUM STRUCTURES.
 -ALL STRUCTURE IS FULLY WELDED WITH A NOMINAL FILLET OF 5mm
 -ALL EXTRUSIONS ARE OF GRADE 6063-T5 OR EQUIVALENT.
 -FILLER ALLOY IS GRADE 5356
 -ALL TIMBER IS TO BE TREATED WITH A SUITABLE PRESERVATIVE.
 (CREOSOTE, DECKING OIL ETC)
 -ALL FASTENERS ARE CORROSION RESISTANT STAINLESS STEEL.
 -ALL EXPOSED BOLTS ARE TO BE RECESSED INTO THE TIMBER BY COUNTER BORING.
 -ALL BOLT THREADS ARE TO BE TREATED WITH ANTI-SIEZE OR EQUIVALENT LUBRICATING COMPOUND, PRIOR TO FASTENING.

SCALE	N.T.S.	DWG	A4-2493	
DRAWN	JPM	REV	A	27,10,00
DATE	27,10,00	CHK		App'D